



**ALS AIRBORNE DUST AND WATER
ANALYSIS AND TESTING REPORT**

REPORT TO: Walker Quarries

REPORT ON: Walker Quarries
Dust & Water Results

REPORT NO: 24005689

PERIOD OF EXPOSURE: Dust - Typically 30 days +/- 2 days
Water - Monthly

SAMPLED BY: ALS Staff

REPORTED BY: Natalie McMillan

REPORT DATE: 15-July-2016



Accreditation # 15784
Site # 11436

Accredited for compliance with ISO/IEC 17025.

This document will not be reproduced except in full.

**ALS AIRBORNE DUST
ANALYSIS AND TESTING REPORT**



WALKER QUARRY

Month Jul-16
Date Replaced 9/06/2016
Date Collected 7/07/2016

DUST DEPOSITION RESULTS

(g/m²/month)

<u>GAUGE NO.</u>	<u>INSOLUBLE SOLIDS</u>	<u>*COMBUSTIBLE MATTER</u>	<u>**ASH</u>
DG#1	1.2	0.4	0.8
DG#2	4.6	3.2	1.4
DG#3	0.3	0.2	0.1
DG#4	19.5	4.4	15.1

No. of days exposed: 28

* Result Calculated
** Incombustible Matter
Analysed in accordance with AS3580.10.1

**ALS AIRBORNE DUST
ANALYSIS AND TESTING REPORT**



WALKER QUARRY

Month Jul-16
Date Replaced 9/06/2016
Date Collected 7/07/2016

DUST GAUGE OBSERVATION

GAUGE	ANALYSIS OBSERVATIONS
DG#1	Clear, insects, fine brown/grey dust & coarse brown/black/grey dust
DG#2	Slightly cloudy, insects, organic matter, fine brown dust & coarse brown/black dust
DG#3	Clear, insects, organic matter, fine brown/grey dust & coarse brown/black dust
DG#4	Slightly cloudy, insects, organic matter, fine brown dust & coarse brown/black/grey/green dust

**ALS WATER
ANALYSIS AND TESTING REPORT**



WALKER QUARRY

	Units		
ALS Sydney Report No.		ES1614871	
Date of Sample		7/07/2016	
Site Reference		Cox's U/S	Cox's D/S
Site Reference		SD3	SD4
Sampled by		J. Takahira & S. McMillan	
General Comments/ Observations		Clear, Mod Flow	Clear, High Flow
Time	24 Hr	9:25	11:20
Temperature	°C	8.6	8.8
pH	pH Unit	8.72	8.84
Electrical Conductivity	µS/cm	1170	1122
Total Suspended Solids	mg/L	<5	<5
Sulphur Sulphate (SO ₄)	mg/L	208	206
Dissolved Metals by ICP-MS			
Manganese	mg/L	0.008	0.005
Iron	mg/L	<0.05	<0.05
Oil & Grease	mg/L	<5	<5

ALS AIRBORNE DUST AND WATER ANALYSIS AND TESTING REPORT

METHODS OF ANALYSIS

Tests for results issued in this report have been carried out at the following NATA accredited laboratories in accordance with the methods as detailed below:-

ACIRL Report No: 24005689

DUST

TEST	METHOD	LABORATORY
		ACIRL Lithgow NATA Accreditation #11436
Dust (Deposited matter gravimetric method)	3580.10.1	X

In accordance with "Methods for sampling and analysis of ambient air.
Method 10.1: Determination of particulate matter- Deposited matter-Gravimetric method"

WATER

TEST	METHOD	LABORATORY	
		ACIRL Lithgow NATA Accreditation #11436	ALS Sydney NATA Accreditation # 825
Electrical Conductivity uS/cm	CBM-E006	X	
pH value	CBM-E005	X	
Total Dissolved Solids	CBM-E007	X	
Total Suspended Solids (mg/l)	CBM-E008	X	
Total Oil & Grease	EP020		X
Manganese	EG020F		X
Iron	EG020F		X
Sulfate (mg/l)	ED014G		X

In accordance with "Standard Methods for the Examination of Water & Wastewater" APHA, AWWA, and Water & Wastewater Examination Manual (V. Dean Adams)

Preservation procedures in accordance with AS/NZS 5667/1 when sampled by ACIRL staff unless otherwise stated.